

CLH...Committed to Cleaner Tomorrow Through Innovation.

## FILLER VALVE - NGV -1 Receptacle



**LD 30**

Make: **OPW Sherex (LD30)**

### MATERIALS:

Body: Stainless Steel

Internal Parts: Stainless Steel and Brass

Seals:

### SPECIFICATIONS:

Min. Flow Rate: 1500 SCFM @ 3000  
psid

Temperature Range: -40° C to 120° C

Weight: 1.33 kg. (2.94 lbs.)

Design Pressure: 5000 psi (345 Bar)

C  
N  
G  
L  
P  
G  
H  
H2



CLH...Committed to Cleaner Tomorrow Through Innovation.

## Filler Valve CL Series



### Material of Filler Valve

**Body and Adaptor Shaft:** Stainless Steel

**Internal Components:** Stainless Steel

**Seals:** Specially formulated polymers and elastomers specific to high pressure NGV applications.

### Technical Details of CL Series Valves

<u>Specification</u>	<u>CL 40</u>	<u>CL50</u>
<b>Minimum Flow Rate</b>	1500 SCFM @ 3000Psid	5000 SCFM @ 3000Psid
<b>Temperature Range</b>	-40° C to 120° C (-40° F to 250° F)	-40° C to 120° C (-40° F to 250° F)
<b>Design Pressure</b>	5000 psi (345 Bar)	5000 psi (345 Bar)
<b>Applications</b>	Small Trucks - LCV	HCV

C  
N  
G  
L  
P  
G  
H  
H2



CLH...Committed to Cleaner Tomorrow Through Innovation.

## EMER FILLER VALVE



NGV 1-P 30

- **NGV 1-P30 receptacle with external thread for Ø6 pipe, M12x1 connection, with stainless steel airtight cap.**
- **Working Pressure : 207 Bar(3000 Psi)**
- **Working Temperature: -40 Deg. C to 120 Deg. C**
- **Minimum Flow Rate: 1500 SCFM @ 3000Psi**
- **Approval: E3-110R-003007**
- **Material: Corrosion Resistant stainless steel**



**NZS**

### Features:

- **Burst Disc Fitting**
- **Burst Disc 300 +/- 10 Bar**
- **Internal connection : M 12 x 1**
- **External connection: G1/2**

C  
N  
G  
L  
P  
G  
H  
H2

